

REACH YOUR DESTINATION BOTH QUICKLY AND SECURELY.

The 3262i and 4062i A3 b/w multifunctional systems race along the fast lane at an output speed of 32 or 40 pages per minute. Optional equipment offers versatile finishing options and original feeders, which make even the longest stretches (of work) a pleasure.

Both systems have a loading volume of up to 4,100 sheets, can staple up to 65 sheets using the finisher* and can sort the printouts by user or department if necessary. The multi tray with up to seven trays ensures you can bypass paper jams and continue your workflow at top speed.



DIGITAL ••• MULTIFUNCTIONAL SYSTEM **3262i / 4062i** Copy / Print / Scan / Fax A3

HIGHLIGHTS:

Extraordinary performance: Both systems work with a high resolution of 1,200 x 1,200 dpi for top-quality prints. The large colour touch display (22.86 cm in size) can be used and adjusted intuitively. Up to 58 function icons can be configured individually. This means that the user can immediately copy or send at the touch of a button and also have faster access to saved print data in the user and print job boxes.

Fantastic flexibility: Choose between three different optional feeders. The main highlight is the dual scanner, which can read a maximum of 160 image pages in one minute. The manual feeder linked to up to five feed sources* facilitates the processing of different types of media, paper formats and paper weights, which can also be output via the default job separator.

Smart networking and security: Alongside software solutions* such as follow-me printing that can be integrated via the HyPAS interface, NFC (Near Field Communication) transmission technology offers enhanced flexibility and increased security. Print jobs can be confirmed and printed via smartphone or tablet authentication with the system. As data transfer is carried out over a short distance, the possibility of unauthorised parties reading your data is minimised. The Data Security Kit* guarantees additional security.

Environmentally friendly technology: Environmental awareness is at the forefront of the 3262i and 4062i multifunctional systems. Both systems were developed and optimised with a view to meeting current environmental requirements in terms of energy efficiency and environmental friendliness. Functions such as duplex printing and automatic skipping for blank pages reinforce this line of thinking, as resources such as paper, toner and time are saved in your everyday workflows.

3262i/4062i

TECHNICAL DATA

General

General	
Туре	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser b/w
Original format	max A3 from platen glass
Copy/print speed	<i>3262i:</i> max 32 A4 pages/min and max 17 A3 pages/min
	4062i: max 40 A4 pages/min and max 21 A3 pages/min
1st page (Copy/ Print)	4.3/4.9 seconds* (3262i), 3.6/4.2 seconds* (4062i)
Warm-up time	18 seconds*
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (A5R-A3), 100 sheet multi-bypass (A6R-A3)
Paper weights	Universal cassette 60-163 g/m², multi-bypass 45-256 g/m², duplex 60-160 g/m²
Paper output	250 sheet A4
Job Separator	Standard, 50 sheet
System memory	2 GB RAM, 32 GB SSD**/ optional: 320 GB HDD** (3262i)
	2 GB RAM, 8 GB SSD**, 320 GB HDD** (4062i)
Continuous copying	1-999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Touch screen, duplex, 1,000 management codes, skip blank pages etc.
Dimensions/Weig	Iht
Dimensions	683 x 594 x 696 mm (H x W x D)
Weight	approx. 59 kg
Environment	
Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,620 W max, approx. 510 W (3262i)/600 W (4062i) in operation, approx. 100 W in stand-by mode, approx. 1 W in sleep mode, TEC value: 1.4/1.9 KWh/week (3262i/4062i)
Safety	gs/tüv, ce

Print System Туре Integrated within the system

Print format A6R-A3

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

Print System Print resolution 1,200 x 1,200 dpi, 9.600 x 600 dpi Freescale QorlQ T1024 (Dual Core) 1.0 GHz Processor USB 2.0, 10/100/1000BaseTX, USB host, Interfaces NFC TCP/IP, Net BEUI Network protocols **Operating systems** Windows 7/8.1/10; Windows Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare***, Linux, Mac ex OS 10.8 Emulations PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 1.7, PRESCRIBE IIe Functions USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, Google Cloud

Print

Scan system

Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 80 (simplex) or 160 (duplex) A4 originals/min in colour and b/w with DP-7110 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interface	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 7/8.1/10; Windows Server 2008/2008 R2/2012/2012 R2/2016
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP
Optional fax syst	em 12
Compatibility	Super G3
Original format	max A3

Unginal IUmat	IIIdx AS
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi



-	170 MD										
Fax memory	170 MB										
Abbreviated dial	2,000 numbers										
One touch dial	1,000 numbers 500 numbers										
Group dial											
Operating systems	Windows 7/8.1/10; Windows Server 2008/2008 R2/2012/2012 R2/2016										
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception										
Options											
Original feeder	DP-7100 document processor with auto- matic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7120 document processor with auto- matic reverse function (A5R-A3, capacity: 50 sheet A4, paper weight 45-160 g/m ²), DP-7110 document processor with simulta neous duplex scanning (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m ²)										
Platen cover	Platen cover type E (if document process is not installed)										
Finisher	DF-7120 (capacity: 1,000 sheet A4, staplin max 50 sheet A4), DF-791 (capacity: 3,000 sheet A4, stapling max 65 sheet A4), PH-7C hole punch unit for DF-7120/DF-79 MT-730 (B) multi tray for DF-791										
Paper feed	PF-791 (2 x 500 sheet universal cassettes [A5R-A3]), PF-810 (2 x 1,500 sheet large capacity cassette [A4])										
Other options	Scan extension kit (A), Data security kit (E), Internet fax kit (A), Card authentication kit (B), Keyboard holder (10), UG-33 ThinPrint@ kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, IB-35 WLAN card, DT-730 (B) Document tray, NK-7100 Numeric Keyboard (10 keys), HD-12 (320 GB HDD**for the 3262i), cabinet no. 70										

*Depending on operating status.

For copy, print, scan, fax. *optional

Specifications subject to change without notice.

Image shows machine with optional accessories.

The 3262i and the 4062i are manufactured in accordance with the requirements of the Energy Star Program.









mopria



1	Yo	ur	۰ı	л	-Δ	х	_	d	2	а	١	> r																	
:																													
:																													