



# Set up your office for the future now

4009ci • 5009ci • 6009ci • 7009ci

**Our A3 multifunctional systems are your ideal partners for intelligent, efficient and future-oriented office work. Find out how seamless integration into cloud-based applications, first-class print quality and user-friendly operation can take your workflows to a whole new level. The 4009ci, 5009ci, 6009ci and 7009ci product ranges offer print and copy speeds from 40, 50, 60 up to 70 A4 pages per minute, in colour or black and white. These systems increase productivity in all working environments thanks to their flexibility, fast print speeds and ability to efficiently manage large print jobs.**

## What you can expect:



**INTELLIGENT CONNECTIVITY:** All systems can be easily integrated into common cloud platforms – from Google Drive to Microsoft SharePoint. This means you can access your documents seamlessly at any time, whether from your office or home office. Document Guard can prevent confidential documents from being scanned or copied – of course, only you decide exactly what and how!



**OPTIMISED PRODUCTIVITY:** If you are looking for professional high-speed digitisation, we recommend the dual scanner with ultrasonic sensor\*, which processes up to 274 image pages per minute at 300 dpi. Not only does the scanning unit detect whether multiple originals are being fed at the same time, and stop the scanning process, it also protects the documents with integrated staple detection\*. Speaking of detection, the print resolution of images can be optimised and reproduced in brilliant quality using AI and the Super Resolution Imaging print function.



**TRANSPARENT ENERGY MANAGEMENT:** The energy consumption of the multifunctional systems can be displayed and monitored transparently on the 10.1 inch touchscreen, allowing you to optimise how you use the systems. In addition to providing energy-efficient toners, we have also increased the proportion of recyclable plastic in our MFPs to reduce the consumption of resources in the circular economy and so further reduce our environmental impact.



**COMPLIANT SECURITY:** Comprehensive hardware protection of the hard drives guarantees that your data is overwritten and encrypted multiple times. The 'Secure Boot' function ensures that only authorised firmware is executed during each start-up. During operation, the 'Run Time Integrity Check' regularly verifies the validity of the firmware. This way, our systems ensure that your data is protected at all times and that malware is successfully repelled.



\* optional



**4009ci • 5009ci • 6009ci • 7009ci**  
**Digital Multifunctional Colour System**  
**Copy / Print / Scan / Fax**  
**A3**

# Technical Data: 4009ci • 5009ci • 6009ci • 7009ci

GENERAL		Noise level	4009ci/5009ci/6009ci/7009ci: approx. (50.3/50) (51.9/51.6) (53.4/53) (54.3/54) dB(A) in operation (colour / b/w-mode), stand-by mode: 30.5/30.3/33.3/31.7 dB(A) (ISO 7779/9296)	Fax memory	170 MB
Type	Desktop	Safety	GS/TÜV, CE	Abbreviated dial	2,000 numbers
Function	Copy, print, scan, optional: fax	PRINT SYSTEM		One touch dial	1,000 numbers
Print technology	Laser colour and b/w	Type	Integrated within the system	Group dial	500 numbers
Original format	max A3	Print format	A6R-SRA3	Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
Copy/print speed	4009ci: max 40 A4 pages/min and max 20 A3 pages/min in colour and b/w 5009ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and b/w 6009ci: max 60 A4 pages/min and max 30 A3 pages/min in colour and b/w 7009ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and b/w	Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi	Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception
1st page (Print/Copy)	Colour: 6.5/5.9 seconds <sup>1</sup> , b/w: 5.1/ 4.5 seconds* (4009ci), Colour: 5.4/4.8 seconds <sup>1</sup> , b/w: 4.3/3.7 seconds* (5009ci), Colour: 5.1/4.4 seconds <sup>1</sup> , b/w: 3.8/ 3.4 seconds* (6009ci), Colour: 5.0/4.4 seconds <sup>1</sup> , b/w: 3.7/3.4 seconds* (7009ci)	Processor	ARM A53 1.6GHz	OPTIONS	
Warm-up time	17 seconds (4009ci/5009ci/6009ci) 26 seconds (7009ci)	Interfaces	USB 3.0, USB-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card Slot	Original feeder	DP-7150 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m <sup>2</sup> ), DP-7160 document processor with simultaneous duplex scanning (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m <sup>2</sup> ), DP-7170 document processor with simultaneous duplex scanning, multi-feed detection and sensor with staple detection (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m <sup>2</sup> )
Copy resolution	600 x 600 dpi	Network protocols	TCP/IP, Net BEUI	Platen cover	Platen cover type E (if document processor is not installed)
Greyscales	256	Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac OS X 10.14	Finisher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4, not available for 7008ci), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7140 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7150 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7140/7150, BF-730 brochure module for DF-7140 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7140, IS-7100 inserter (available for 6009ci/7009ci), ZF-7100 Z-fold unit (available for 6009ci/7009ci)
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing	Emulations	PCL6 (Se, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIc	Job separator	
Paper weights	Universal cassette 52-300 g/m <sup>2</sup> , multi-bypass 52-300 g/m <sup>2</sup> , duplex 64-256 g/m <sup>2</sup>	Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/ Apple AirPrint, NFC, Wi-Fi Direct <sup>3</sup>	Paper feed	PF-7140 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7150 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
Paper output	500 sheet A4	SCAN SYSTEM		Other options	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-53 Gigabit Ethernet card, IB-54 WLAN card (IEEE802.11b/g/n, Wi-Fi direct, WPA3), IB-37 WLAN card (IEEE802.11a/b/g/n/ ac, Wi-Fi direct) or IB-38 WLAN* card (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 81, HD-15 (320 GB HDD <sup>1</sup> ), HD-16 (1 TB HDD <sup>2</sup> ), Fiery® Controller (Printing System 17)
System memory	4 GB RAM, 128 GB SSD/optional: 320 GB or 1 TB HDD <sup>2</sup>	Scan type	CCD colour and b/w	<sup>1</sup> Depending on operating status <sup>2</sup> For copy, print, scan, fax <sup>3</sup> optional <sup>4</sup> IB-38 is only available for selected countries outside the EU that do not support the IB-37	
Continuous copying	1-9,999 copies	Scan format	max A3		
Zoom	25 %-400 % in steps of 1 %	Scan speed	max 137 (simplex) or 274 (duplex) A4 originals/min in colour and b/w with DP-7170 (300 dpi)		
Functions	Adjustable colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), trusted platform module (TPM), secure boot und runtime integrity check, simple certificate enrollment protocol (SCEP), TLS 1.3, OCSP, CRL, S/MIME, SIEM-Support, Allowlisting, fax server connectivity etc.	Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi		
DIMENSIONS/WEIGHT		Scan mode	Photo, text, photo/text, optimised for OCR	<b>OPTIONAL FAXSYSTEM 12</b>	
Dimensions	790 x 602 x 665 mm (H x W x D)	File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS		
Weight	approx. 95 kg	Interface	10/100/1000BaseTX		
ENVIRONMENT		Network protocol	TCP/IP		
Mains voltage	220/240 V, 50/60 Hz	Operating systems	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	<b>COMPATIBILITY</b>	
Power consumption	approx. 1,750 W (2,400 W - 7008ci) max, approx. 660/780/990/1,140 W in operation (4009ci/5009ci/6009ci/7009ci), approx. 45 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.51/0.63/0.79/1.01 kWh/week (4009ci/5009ci/6009ci/7009ci)	Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, multi crop scan, handwriting enhancement, document guard, cloud capture functionality, image defect prevention, ID-scan		
		Modem speed	33.6 kbps		
		Transmission speed	3 seconds or less using JBIG		
		Compression method	JBIG, MMR, MR, MH		
		Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi		








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.

TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.