

Umweltdatenblatt

P-C2157w MFP

Umweltmanagement	Die Fertigung dieses Geräts erfolgt in Produktionsstätten, die mit einem Umweltmanagementsystem gem. ISO 14001 arbeiten.		
Umweltzertifikat	Blauer Engel nach DE-UZ 219 in Bearbeitung		
Leistungsaufnahme Wärmeabgabe		Leistungsaufnahme	Wärmeabgabe
	Maximal (beim Einschalten, „inkl. Optionen“):		
		1066 W	3838 kJ/h
	Drucken:	345 W	1242 kJ/h
	Bereit:	41 W	148 kJ/h
	Ruhemodus:	0,4 W	1,4 kJ/h
	Schalter-Aus:	0,1 W	0,4 kJ/h
Typischer Stromverbrauch (TEC)	0,20 kWh/Woche (ermittelt gem. ENERGY STAR 3.2)		
Aufstellhinweise	Das Multifunktionsgerät sollte so aufgestellt werden, dass sowohl seitlich, als auch vor und hinter dem System ausreichend Platz für die Bedienung und zur Wartung freigehalten wird. Für eine gute Belüftung sorgen. Das MFP-System nicht in staubigen Räumen aufstellen und vor Ammoniakdämpfen schützen. Bitte beachten Sie die Hinweise im Anwenderhandbuch.		
Luftfeuchtigkeit	10% - 80%		
Raumtemperatur	10°C - 32,5°C		
Geräuschemission (gem. ISO 7779 / ISO 9296)	Surface sound pressure level (Messung in 1m Entfernung, Durchschnitt aus Einzelmessungen) Betrieb (SW-/Farbmodus): 45,2 dB(A) L _{pA} 45,8 dB(A) L _{pA} Bereit: nicht messbar Operator position (Messung in Bedienerposition) Betrieb (SW-/Farbmodus): 50,5 dB(A) L _{pA} 51,4 dB(A) L _{pA} Bereit: nicht messbar Garantierter A-bewerteter Schallleistungspegel entsprechend DE-UZ 219 Betrieb (SW-/Farbmodus): 61,2 dB(A) L _{WAc} 61,8 dB(A) L _{WAc} Garantierter A-bewerteter Schallleistungspegel in Anlehnung an DE-UZ 219 Bereit: nicht messbar		
Lichtquelle	Belichtung Trommel: Laser		
Emissionen	nach DE-UZ 219 (Farbmodus) TVOC (Betrieb): 3,15 mg/h TVOC (Bereit): 0,028 mg/h Benzol: 0,01 mg/h Styrol: 0,07 mg/h Ozon: 0,24 mg/h Staub: < Bestimmungsgrenze		

Environmental Data Sheet

P-C2157w MFP

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.																																
Environmental Label	Blue Angel DE-UZ 219 in preparation																																
Power Consumption Heat Emission	<table><tr><td></td><td>Power Consumption</td><td>Heat Emission</td></tr><tr><td>Maximum (at switch on, full options):</td><td>1066 W</td><td>3838 kJ/h</td></tr><tr><td>Printing:</td><td>345 W</td><td>1242 kJ/h</td></tr><tr><td>Ready:</td><td>41 W</td><td>148 kJ/h</td></tr><tr><td>Sleep mode:</td><td>0.4 W</td><td>1.4 kJ/h</td></tr><tr><td>Off-mode:</td><td>0.1 W</td><td>0.4 kJ/h</td></tr></table>				Power Consumption	Heat Emission	Maximum (at switch on, full options):	1066 W	3838 kJ/h	Printing:	345 W	1242 kJ/h	Ready:	41 W	148 kJ/h	Sleep mode:	0.4 W	1.4 kJ/h	Off-mode:	0.1 W	0.4 kJ/h												
	Power Consumption	Heat Emission																															
Maximum (at switch on, full options):	1066 W	3838 kJ/h																															
Printing:	345 W	1242 kJ/h																															
Ready:	41 W	148 kJ/h																															
Sleep mode:	0.4 W	1.4 kJ/h																															
Off-mode:	0.1 W	0.4 kJ/h																															
TEC	0.20 kWh/week (determined according to ENERGY STAR 3.2)																																
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the unit in dusty rooms, and protect against ammonia vapours. Please follow the instructions in the user manual.																																
Humidity	10% - 80%																																
Room Temperature	10°C – 32.5°C																																
Noise Emission (According to ISO 7779 / ISO 9296)	<table><tr><td colspan="3">Surface sound pressure level (Measurement in 1 m distance; average of single measurements)</td></tr><tr><td>Operation (BW/colour):</td><td>45.2 dB(A) L_{pA}</td><td>45.8 dB(A) L_{pA}</td></tr><tr><td>Ready:</td><td colspan="2">not measurable</td></tr><tr><td colspan="3">Operator position</td></tr><tr><td>Operation (BW/colour):</td><td>50.5 dB(A) L_{pA}</td><td>51.4 dB(A) L_{pA}</td></tr><tr><td>Ready:</td><td colspan="2">not measurable</td></tr><tr><td colspan="3">Declared A-weighted sound power level according to DE-UZ 219</td></tr><tr><td>Operation (BW/colour):</td><td>61.2 dB(A) L_{WAc}</td><td>61.8 dB(A) L_{WAc}</td></tr><tr><td colspan="3">Declared A-weighted sound power level following DE-UZ 219</td></tr><tr><td>Ready:</td><td colspan="2">not measurable</td></tr></table>			Surface sound pressure level (Measurement in 1 m distance; average of single measurements)			Operation (BW/colour):	45.2 dB(A) L _{pA}	45.8 dB(A) L _{pA}	Ready:	not measurable		Operator position			Operation (BW/colour):	50.5 dB(A) L _{pA}	51.4 dB(A) L _{pA}	Ready:	not measurable		Declared A-weighted sound power level according to DE-UZ 219			Operation (BW/colour):	61.2 dB(A) L _{WAc}	61.8 dB(A) L _{WAc}	Declared A-weighted sound power level following DE-UZ 219			Ready:	not measurable	
Surface sound pressure level (Measurement in 1 m distance; average of single measurements)																																	
Operation (BW/colour):	45.2 dB(A) L _{pA}	45.8 dB(A) L _{pA}																															
Ready:	not measurable																																
Operator position																																	
Operation (BW/colour):	50.5 dB(A) L _{pA}	51.4 dB(A) L _{pA}																															
Ready:	not measurable																																
Declared A-weighted sound power level according to DE-UZ 219																																	
Operation (BW/colour):	61.2 dB(A) L _{WAc}	61.8 dB(A) L _{WAc}																															
Declared A-weighted sound power level following DE-UZ 219																																	
Ready:	not measurable																																
Light Source	Exposure drum: Laser																																
Emissions	<table><tr><td colspan="2">According to DE-UZ 219 (colour)</td></tr><tr><td>TVOC (Operation):</td><td>3.15 mg/h</td></tr><tr><td>TVOC (Ready):</td><td>0.028 mg/h</td></tr><tr><td>Benzene:</td><td>0.01 mg/h</td></tr><tr><td>Styrene:</td><td>0.07 mg/h</td></tr><tr><td>Ozone:</td><td>0.24 mg/h</td></tr><tr><td>Dust:</td><td>< Limit of quantitation</td></tr></table>			According to DE-UZ 219 (colour)		TVOC (Operation):	3.15 mg/h	TVOC (Ready):	0.028 mg/h	Benzene:	0.01 mg/h	Styrene:	0.07 mg/h	Ozone:	0.24 mg/h	Dust:	< Limit of quantitation																
According to DE-UZ 219 (colour)																																	
TVOC (Operation):	3.15 mg/h																																
TVOC (Ready):	0.028 mg/h																																
Benzene:	0.01 mg/h																																
Styrene:	0.07 mg/h																																
Ozone:	0.24 mg/h																																
Dust:	< Limit of quantitation																																