

It's not artificial intelligence yet – but it's pretty damn close.

The pressure to perform in the office is ever increasing, but fortunately there are now employees who can handle this with ease. Introducing the innovative 4008ci/5008ci/6008ci/7008ciA3 colour MFPs. Breaking new barriers in speed (up to 70 A4 pages/minute), setting standards with their environmental impact and brilliant print quality, as well as being able to sort, check (via ultrasonic sensor and staple detection) and fold – simply incredible. All whilst guaranteeing the highest level of discretion and security, but best of all, they don't spill coffee when under pressure.

HIGHLIGHTS:

Time-saving: Capture individual documents, receipts or sales slips for travel expenses and report them quickly and easily with the integrated MultiCrop receipt scanning function. In just one step, it can digitally cut, straighten, and scan up to 16 receipts simultaneously and then store them separately as a file. A great relief, especially for small-format and non-standardised originals! For professional high-speed digitalisation, we recommend our Dual Scanner with ultrasonic sensors^{*}, which can process up to 274 image pages per minute (300 dpi). The scanning unit not only detects and stops the scanning process when multiple originals are fed in, but also protects them at the same time thanks to its innovative staple detection.

Multi-layered: The systems not only process a wide range of paper weights (52-300 g/m²) and formats (A6R-SRA3), but also offer extensive finishing options. The Job Separator provides a better overview thanks to the internal offset output*, where print jobs or other outputs are sorted to either offset to the left or right, making for easy removal. Various finishers with a stapling function* are available for professional paper management creating less manual work, and in combination with the brochure and/or Z-fold module, your business letters can be folded to fit the length envelope.

More climate-friendly: Thanks to the new toner technology, the toner melting temperature is significantly reduced, this means that the heating elements use less energy to implement the printing process. Low energy requirements mean fewer emissions, less energy consumption and, incidentally, protection of the climate and your wallet.

Play it safe: A standard feature of the system is that it can overwrite and delete print, scan, and copy data multiple times, as well as current encryption protocols such as TLS 1.3 allowing for secure data transmission on the Internet. The USB card readers* provide additional security by automatically verifying your identity on the multifunctional system using a contactless card or transponder.



DIGITAL 🥌 🗣 🗢 🌢 MULTIFUNCTIONAL COLOUR SYSTEM

4008ci / 5008ci / 6008ci / 7008ci

Copy / Print / Scan / Fax A3

4008ci/5008ci/6008ci/7008ci

TECHNICAL DATA

Functions

Dimensions

Mains voltage

Noise level

Safety

ENVIRONMENT

Power consumption

Weight

DIMENSIONS/WEIGHT

recificae				
GENERAL		PRINT SYSTEM		OP
Туре	Desktop	Туре	Integrated within the system	Origi
Function	Copy, print, scan, optional: fax	Print format	A6R-SRA3	
Print technology	Laser colour and b/w	Print resolution	600 x 600 dpi,	
Original format	max A3 from platen glass		max 4,800 equivalent x 1,200 dpi	
Copy/print speed	4008ci: max 40 A4 pages/min and max 20 A3 pages/min in colour and b/w	Processor Interfaces	ARM A53 1.6GHz USB 3.0, USB-Host(4), Gigabit-Ethernet	
	5008ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and b/w	Network protocols	(10/100/1000BaseTX), SD-Card Slot TCP/IP, Net BEUI	
	6008ci: max 60 A4 pages/min and max 30 A3 pages/min in colour and b/w	Operating systems Windows 7/8.1/10, Server 2008/	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell	Plate
1st page	7008ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and b/w Colour: 6.5/5.9 seconds*.	Emulations	NetWare***, Linux, Mac ex OS 10.9 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIc	Finisl
(Print/Copy)	b/w: 5.1/ 4.5 seconds* (4008ci), Colour: 5.4/4.8 seconds*, b/w: 4.3/3.7 seconds* (5008ci), Colour: 5.1/4.4 seconds*, b/w: 3.8/ 3.4 seconds* (6008ci),	Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, NFC, Wi-Fi Direct***	
	Colour: 5.0/4.4 seconds*, b/w: 3.7/3.4 seconds* (7008ci)	SCAN SYSTEM		
Warm-up time	17 seconds (4008ci/5008ci/6008ci) 26 seconds (7008ci)	Scan type Scan format	CCD colour and b/w max A3	
Copy resolution	600 × 600 dpi	Scan speed	max 137 (simplex) or 274 (duplex) A4	
Greyscales	256	Scan speed	originals/min in colour and b/w with DP-7170 (300 dpi)	
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3	Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi	
	(320 x 450 mm)), 150 sheet multi-bypass Scan mode (AGR-SRA3, Banner (305 x 1.219 mm)), SRA3 and banner only for printing File types	Scan mode	Photo, text, photo/text, optimised for OCR	Job S
Demonstration		File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS	
Paper weights	Universal cassette 52-300 g/m², multibypass 52-300 g/m², duplex 60-256 g/m²	Interface	10/100/1000BaseTX	Pape
Paper output	500 sheet A4	Network protocol	TCP/IP	
System memory	4 GB RAM, 64 GB SSD/optional: 320 GB or 1 TB HDD**	Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019	
Continuous copying		Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP	Other
Zoom	25 %-400 % in steps of 1 %		authentication, LDAP, Multiple cropping, Handwriting enhancement	

C

OPTIONAL FAX SYSTEM 12				
Compatibility	Super G3			
Original format	max A3			
Modem speed	33.6 kbps			
Transmission speed	3 seconds or less using JBIG			
Compression method	JBIG, MMR, MR, MH			
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi			
Fax memory	170 MB			
Abbreviated dial	2,000 numbers			
One touch dial	1,000 numbers			
Group dial	500 numbers			
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019			
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception			

Handwriting enhancement

IF IT WORX, IT'S UTAX

PTIONS	
ginal feeder	DP-7150 document processor with automatic reverse function (AGR-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²). DP-7160 document processor with simultaneous duplex scanning (AGR-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²). DP-7170 document processor with simultaneous duplex scanning and multi-feed detection (AGR-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²)
iten cover	Platen cover type E (if document processor is not installed)
isher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4, not available for 7008ci). DF-7120 (capacity: 1.000 sheet A4, stapling max 50 sheet A4). DF-7140 (capacity: 4.000 sheet A4). Stapling max 65 sheet A4). DF-7150 (capacity: 4.000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7140/7150, BF-730 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7140, IS-7100 Inserter (available for 6008(1/7008ci), ZF-7100 Z-fold unit (available for 6008ci/7008ci)
Separator	JS-7100 (100 sheet, 52-300 g/m², A6R - SRA3), JS-7110 inner shift tray (250 sheet, 52-300 g/m², A6R - SRA3)
per feed	PF-7140 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7150 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
ner options	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card (IEEE802.11/b/g/n), IB-37 WLAN card (IEEE802.11/b/g/n/Jac, Wi-Fi direct) or IB-38 WLAN card**** (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 81, HD-15 (320 GB HDD**), HD-16 (1 TB HDD**), Fiery® Controller (Printing System 17)

* Depending on operating status

** For copy, print, scan, fax

*** optional

Your UTAX-dealer

IB-38 is only available for selected countries outside the EU that do not support the IB-37 ***

Specifications subject to change without notice.

Image shows machine with optional accessories.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

GS/TÜV, CE

Adjustable capacitive colour touch screen (10.1 inch), duplex, 1,000 management

codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), secure boot, run time

integrity check, trusted platform modul (TPM), S/MIME etc.

approx. 1.750 W (2,400 W - 7008ci) max, approx. 660/780/990/1,140 W in operation (4008ci/5008ci/6008ci/7008ci).

approx. 45 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.51/0.63/0.79/1.01 KWh/week

4UUBCI/5008ci/6008ci/7008ci: approx. (50.3/50) (51.9/51.6) (53.4/53) (54.3/54) dB(A) in operation (colour / b/w-mode), stand-by mode: 30.5/30.3/33.3/31.7 dB(A) (ISO 7779/9296)

(4008ci/5008ci/6008ci/7008ci)

790 x 602 x 665 mm (H x W x D)

approx. 95 kg

220/240 V, 50/60 Hz











R