

PRODUCT OVERVIEW

05-2025

TA // COLOR AND MONO MULTIFUNCTIONAL SYSTEMS



Content

Color Systems

A3 Multifunctional Systems	page 3
A4 Multifunctional Systems	page 5
A4 Print Systems	page 8

Mono Systems

A3 Multifunctional Systems	page 9
A4 Multifunctional Systems	page 11
A3 Print Systems	page 15
A4 Print Systems	page 16

A3 Multifunctional Systems

Optional features are marked in grey font.



		P-C2480i MFP	2509ci	3509ci	4009ci
COPY	COPY SPEED	24 A4 / 12 A3 pages/min in colour and b/w	25 A4 / 12 A3 pages/min in colour and b/w	35 A4 / 17 A3 pages/min in colour and b/w	40 A4 / 20 A3 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (500 + 100 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	OPTIONAL PAPER FEED	1 or 2 x 500 sheets	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	1,600 sheets	7,150 sheets	7,150 sheets	7,150 sheets
	PAPER FORMAT	A6R-A3	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	ORIGINAL FEEDER	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.5 GB (max 3 GB)	4 GB RAM, 64 GB SSD/320 GB or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB or 1 TB HDD	4 GB RAM, 128 GB SSD/320 GB or 1 TB HDD
ZOOM	25%-400%	25%-400%	25%-400%	25%-400%	
CABINET	Option: no. 62	Option: no. 81	Option: no. 81	Option: no. 81	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000	1,000/2,000

A3 Multifunctional Systems



Optional features are marked in grey font.

		5009ci	6009ci	7009ci	8307ci
COPY	COPY SPEED	50 A4 / 25 A3 pages/min in colour and b/w	60 A4 / 30 A3 pages/min in colour and b/w	70 A4 / 35 A3 pages/min in colour and b/w	70/83 A4 / 35/41 A3 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	7,150 sheets	7,650 sheets	7,650 sheets	7,650 sheets
	PAPER FORMAT	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+
	ORIGINAL FEEDER	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: no. 81	Option: no. 81	Option: no. 81	--	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

A4 Multifunctional Systems

Optional features are marked in grey font.



		302ci	352ci	402ci	502ci
COPY	COPY SPEED	30 A4 pages/min. in colour and b/w	35 A4 pages/min. in colour and b/w	40 A4 pages/min. in colour and b/w	50 A4 pages/min. in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets
	PAPER CAPACITY, MAX	3,100 sheets	3,100 sheets	3,100 sheets	3,100 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.536 MB RAM (max 3.072 MB RAM)	4 GB RAM, 16 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD
ZOOM	25%-400%	25%-400%	25%-400%	25%-400%	
CABINET	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2)	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB-Host (3), NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016/2019, Novell NetWare, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A4	max A4	max A4	max A4
	MODEM SPEED	33,6 kbps	33,6 kbps	33,6 kbps	33,6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000	1,000/2,000

A4 Multifunctional Systems

Optional features are marked in grey font.



		P-C2157w MFP	P-C2656w MFP	358ci	458ci
COPY	COPY SPEED	21 A4 pages/min in colour and b/w	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	45 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	350 (1 x 250 + 100 sheets)	650 (1 x 550 + 100 sheets)
	OPTIONAL PAPER FEED	1 x 250 sheets	1 x 250 sheets	3 x 550 sheets	4 x 550 sheets
	PAPER CAPACITY, MAX	550 sheets	550 sheets	2,000 sheets	2,850 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (RDF)	Standard (Duplex Scan)	Standard (dual scan)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 1 GB)	1 GB RAM (max 1 GB)	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: no. 77	Option: no. 77	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CIS colour and b/w	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A4	max A4	max A4	max A4
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	100/200	100/200	100/200

A4 Multifunctional Systems

Optional features are marked in grey font.



		P-C3563i MFP	P-C3567i MFP	P-C4063i MFP	P-C4067i MFP
COPY	COPY SPEED	35 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	3 x 550 sheets	3 x 550 sheets	3 x 550 sheets	3 x 550 sheets
	PAPER CAPACITY, MAX	2,000 sheets	2,000 sheets	2,000 sheets	2,000 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (dual scan)	Standard (dual scan)	Standard (dual scan with multi-feed detection)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.5 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	1.5 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDLL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS	PCL6 (5c, XL), KPDLL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS	PCL6 (5c, XL), KPDLL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS	PCL6 (5c, XL), KPDLL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 1.7, XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4	--	max A4
	MODEM SPEED	--	33.6 kbps	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200	--	100/200

A4 Print Systems



P-C2651DW

PRINT FORMAT	A6R-A4
PRINT SPEED	26 A4 pages/min in colour and b/w
PRINT RESOLUTION	600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed)
STANDARD PAPER FEED	300 (1 x 250 + 50 sheets)
OPTIONAL PAPER FEED	1 x 250 sheets
DUPLEX	Standard
PROCESSOR	Cortex-A9 / 800 MHz
PRINT MEMORY	1 GB RAM (max 1 GB RAM)
INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi
NETWORK CARD OPTIONAL	--
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS



P-C3563DN

PRINT FORMAT	A6R-A4
PRINT SPEED	35 A4 pages/min in colour and b/w
PRINT RESOLUTION	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
STANDARD PAPER FEED	650 (1 x 550 + 100 sheets)
OPTIONAL PAPER FEED	3 x 550 sheets
DUPLEX	Standard
PROCESSOR	ARM Cortex-A9 dual core/1.2 GHz
PRINT MEMORY	1 GB RAM (max 1 GB RAM)
INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)
NETWORK CARD OPTIONAL	IB-50 Gigabit Ethernet, IB-37/IB-51 WLAN card
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



P-C4063DN

PRINT FORMAT	A6R-A4
PRINT SPEED	40 A4 pages/min in colour and b/w
PRINT RESOLUTION	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
STANDARD PAPER FEED	650 (1 x 550 + 100 sheets)
OPTIONAL PAPER FEED	3 x 550 sheets
DUPLEX	Standard
PROCESSOR	ARM Cortex-A9 dual core/1.2 GHz
PRINT MEMORY	1 GB RAM (max 3 GB RAM)
INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)
NETWORK CARD OPTIONAL	IB-50 Gigabit Ethernet, IB-37/IB-51 WLAN card
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



P458ci

PRINT FORMAT	A6R-A4
PRINT SPEED	45 A4 pages/min in colour and b/w
PRINT RESOLUTION	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
STANDARD PAPER FEED	650 (1 x 550 + 100 sheets)
OPTIONAL PAPER FEED	4 x 550 sheets
DUPLEX	Standard
PROCESSOR	ARM Cortex-A9 dual core/1.2 GHz
PRINT MEMORY	1 GB RAM (max 3 GB RAM)
INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)
NETWORK CARD OPTIONAL	IB-50 Gigabit Ethernet, IB-37/IB-51 WLAN card
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS

A3 Multifunctional Systems

Optional features are marked in grey font.



		P-2540i MFP	3263i	4063i
COPY	COPY SPEED	25 A4 / 12 A3 pages/min	32 A4 / 17 A3 pages/min	40 A4 / 21 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	1 or 2 x 500 sheets	2 x 500 sheets or 2 x 1,500 sheets	2 x 500 sheets or 2 x 1,500 sheets
	PAPER CAPACITY, MAX	1,600 sheets	4,100 sheets	4,100 sheets
	PAPER FORMAT	A6R-A3	A6R-A3	A6R-A3
	ORIGINAL FEEDER	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB (max 3 GB)	4 GB RAM, 32 GB SSD / 320 GB or 1 TB HDD	4 GB RAM, 32 GB SSD / 320 GB or 1 TB HDD
ZOOM	25%-400%	25%-400%	25%-400%	
CABINET	Option: no. 22	Option: no. 70	Option: no. 70	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB-host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB-host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe, PDF 1.7	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000

A3 Multifunctional Systems

Optional features are marked in grey font.



		5059i	6059i	7059i	8057i
COPY	COPY SPEED	50 A4 / 25 A3 pages/min	60 A4 / 30 A3 pages/min	70 A4 / 35 A3 pages/min	80 A4 / 40 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	7,150 sheets	7,650 sheets	7,650 sheets	7,650 sheets
	PAPER FORMAT	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+
	ORIGINAL FEEDER	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB	4 GB RAM, 128 GB SSD/320 GB HDD or 1 TB	4.5 GB RAM, 8 GB SSD/320 GB HDD
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: no. 81	Option: no. 81	Option: no. 81	--	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

A4 Multifunctional Systems



P-3521 MFP

P-3527w MFP

COPY	COPY SPEED	35 A4 pages/min	35 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	2 x 250 sheets	2 x 250 sheets
	PAPER CAPACITY, MAX	850 sheets	850 sheets
	PAPER FORMAT	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Standard
	DUPLEX	Standard	Standard
	SYSTEM MEMORY	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
ZOOM	25%–400%	25%–400%	
CABINET	Option: no. 78	Option: no. 78	
PRINT	TYPE	Integrated within the system	Integrated within the system
	INTERFACES	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9
EMULATIONS	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CIS colour and b/w	CIS colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4
	MODEM SPEED	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200

A4 Multifunctional Systems



		P-4021 MFP	P-4026w MFP	P-4027iw MFP
COPY	COPY SPEED	40 A4 pages/min	40 A4 pages/min	40 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
	PAPER CAPACITY, MAX	850 sheets	850 sheets	850 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (Duplex Scan)	Standard (Duplex Scan)	Standard (Duplex Scan)
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 1 GB RAM)	1 GB RAM (max 1 GB RAM)	2 GB RAM (max 2 GB RAM)
ZOOM	25%-400%	25%-400%	25%-400%	
CABINET	Option: no. 78	Option: no. 78	Option: no. 78	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CIS colour and b/w	CIS colour and b/w	CIS colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4	max A4
	MODEM SPEED	--	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200	100/200

A4 Multifunctional Systems

Optional features are marked in grey font.



		P-4532 MFP	P-4539 MFP	P-4532i MFP	P-4539i MFP
COPY	COPY SPEED	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	PAPER CAPACITY, MAX	2,600 sheets	2,600 sheets	2,600 sheets	2,600 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Standard	Standard	Standard
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 3 GB RAM), 64/256/512 GB SSD	1 GB RAM (max 3 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
PRINT	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	ORIGINALS	--	max A4	--	max A4
	MODEM SPEED	--	33.6 kbps	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	22/100	--	100/200

A4 Multifunctional Systems

Optional features are marked in grey font.



		P-5539i MFP	P-6039i MFP
COPY	COPY SPEED	55 A4 pages/min	60 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets
	PAPER CAPACITY, MAX	2,600 sheets	2,600 sheets
	PAPER FORMAT	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (Duplex Scan)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard
	SYSTEM MEMORY	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	
CABINET	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
PRINT	TYPE	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host, SD slot
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
NETWORK	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
SCAN	SCAN TYPE	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP
FAX	ORIGINALS	max A4	max A4
	MODEM SPEED	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	100/200

A3 Print Systems



P-6040DN

PRINT FORMAT	A6R-SRA3
PRINT SPEED	60 A4 / 30 A3 pages/min
PRINT RESOLUTION	1,200 x 1,200 dpi
STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)
OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets
DUPLEX	Standard
PROCESSOR	Freescale QoriQ T1024 (Dual Core) 1.2 GHz
PRINT MEMORY	4 GB RAM, 8 GB SSD, 320 GB HDD
INTERFACES	USB 2.0, USB host, 10/100/1000BaseTX, NFC
INTERFACES OPTIONAL	--
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PDF 1.7, PRESCRIBE IIe, XPS

A4 Print Systems



P-3522DW

- PRINT FORMAT**
- PRINT SPEED**
- PRINT RESOLUTION**
- STANDARD PAPER FEED**
- OPTIONAL PAPER FEED**
- DUPLEX**
- PROCESSOR**
- PRINT MEMORY**
- INTERFACES**
- INTERFACES OPTIONAL**
- EMULATIONS**

A6R-A4
 35 A4 pages/min
 600 x 600 dpi, 1,200 x 1,200 dpi
 350 (250 + 100 sheets)
 2 x 250 sheets
 Standard
 Cortex-A9 / 800 MHz
 256 MB (max 256 MB)
 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
 --
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



P-4021DN

A6R-A4
 40 A4 pages/min
 600 x 600 dpi, 1,200 x 1,200 dpi
 350 (250 + 100 sheets)
 2 x 250 sheets
 Standard
 Cortex-A9 / 800 MHz
 512 MB RAM (max 512 MB RAM)
 10/100/1000BaseTX, USB 2.0, USB host, SD slot
 --
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

P-4021DW

A6R-A4
 40 A4 pages/min
 600 x 600 dpi, 1,200 x 1,200 dpi
 350 (250 + 100 sheets)
 2 x 250 sheets
 Standard
 Cortex-A9 / 800 MHz
 512 MB RAM (max 512 MB RAM)
 10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
 --
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



P-4534DN

- PRINT FORMAT**
- PRINT SPEED**
- PRINT RESOLUTION**
- STANDARD PAPER FEED**
- OPTIONAL PAPER FEED**
- DUPLEX**
- PROCESSOR**
- PRINT MEMORY**
- INTERFACES**
- INTERFACES OPTIONAL**
- EMULATIONS**

A6R-A4
 45 A4 pages/min
 1,200 x 1,200 dpi
 600 (500 + 100 sheets)
 4 x 500 sheets
 Standard
 ARM Cortex-A53 Dual Core, 1,4 GHz
 512 MB (max 2.5 GB)
 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
 IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



P-5034DN


A6R-A4
 50 A4 pages/min
 1,200 x 1,200 dpi
 600 (500 + 100 sheets)
 4 x 500 sheets
 Standard
 ARM Cortex-A53 Dual Core, 1,4 GHz
 512 MB (max 2.5 GB)
 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
 IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

P-5534DN

A6R-A4
 55 A4 pages/min
 1,200 x 1,200 dpi
 600 (500 + 100 sheets)
 4 x 500 sheets
 Standard
 ARM Cortex-A53 Dual Core, 1,4 GHz
 512 MB (max 2.5 GB)
 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
 IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

P-6034DN

A6R-A4
 60 A4 pages/min
 1,200 x 1,200 dpi
 600 (500 + 100 sheets)
 4 x 500 sheets
 Standard
 ARM Cortex-A53 Dual Core, 1,4 GHz
 512 MB (max 2.5 GB)
 10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
 IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
 PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



We develop **individual processes in the fields of document solutions, information and IT**. Document technology is our core business and we continuously develop our portfolio. At the same time, we assist our customers in creating flexible and modern workplaces with our pioneering mobile solutions and cloud services. Efficient processes are crucial for the success of a company. **We can assist you with solutions for saving time and money with your workflows** and support you with our expertise in implementing professional hardware and software solutions.