

4008ci / 5008ci / 6008ci / 7008ci

Efficiency made even more efficient.

Fast print processing, complex finishing options and increased simplification in the digitalisation process, these are just a few of the brilliant features that our A3 colour multifunctional systems possess. The 4008ci, 5008ci, 6008ci and 7008ci product family prints and copies at speeds of 40, 50, 60 and 70 A4 pages/minute in colour and b/w. The tiltable 10.1-inch (25.6cm) colour touch display will not only impress you with its elegant design, optimised menu navigation and intuitive operation, but also with its zoom function and enlarged LED displays, providing greater orientation on the system in next to no time.

What you can expect:



Timesaving: Capture individual documents, receipts or sales slips for travel expenses and report them quickly and easily with the integrated MultiCrop receipt scanning function. In just one step, it can digitally cut, straighten, and scan up to 16 receipts simultaneously and then store them separately as a file. A great relief, especially for small-format and non-standardised originals! For professional high-speed digitalisation, we recommend our Dual Scanner with ultrasonic sensors*, which can process up to 274 image pages per minute (300 dpi). The scanning unit not only detects and stops the scanning process when multiple originals are fed in, but also protects them at the same time thanks to its innovative staple detection.



Multi-layered: The systems not only process a wide range of paper weights (52-300 g/m²) and formats (A6R-SRA3), but also offer extensive finishing options. The Job Separator provides a better overview thanks to the internal offset output*, where print jobs or other outputs are sorted to either offset to the left or right, making for easy removal. Various finishers with a stapling function* are available for professional paper management creating less manual work, and in combination with the brochure and/or Z-fold module, your business letters can be folded to fit the length envelope.



More climate-friendly: Thanks to the new toner technology, the toner melting temperature is significantly reduced, this means that the heating elements use less energy to implement the printing process. Low energy requirements mean fewer emissions, less energy consumption and, incidentally, protection of the climate and your wallet.



Play it safe: A standard feature of the system is that it can overwrite and delete print, scan, and copy data multiple times, as well as current encryption protocols such as TLS 1.3 allowing for secure data transmission on the Internet. The USB card readers* provide additional security by automatically verifying your identity on the multifunctional system using a contactless card or transponder.



* optional



4008ci / 5008ci / 6008ci / 7008ci
Digital multifunctional colour system
Copy / Print / Scan / Fax
A3

4008ci / 5008ci / 6008ci / 7008ci

Technical data

GENERAL

Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser colour and b/w
Original format	max A3 from platen glass
Copy/print speed	4008ci: max 40 A4 pages/min and max 20 A3 pages/min in colour and b/w 5008ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and b/w 6008ci: max 60 A4 pages/min and max 30 A3 pages/min in colour and b/w 7008ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and b/w
1st page (Print/Copy)	Colour: 6.5/5.9 seconds*, b/w: 5.1/ 4.5 seconds* (4008ci), Colour: 5.4/4.8 seconds*, b/w: 4.3/3.7 seconds* (5008ci), Colour: 5.1/4.4 seconds*, b/w: 3.8/ 3.4 seconds* (6008ci), Colour: 5.0/4.4 seconds*, b/w: 3.7/3.4 seconds* (7008ci)
Warm-up time	17 seconds (4008ci/5008ci/6008ci) 26 seconds (7008ci)
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing
Paper weights	Universal cassette 52-300 g/m ² , multibypass 52-300 g/m ² , duplex 60-256 g/m ²
Paper output	500 sheet A4
System memory	4 GB RAM, 64 GB SSD/optional: 320 GB or 1 TB HDD**
Continuous copying	1-9,999 copies
Zoom	25 % - 400 % in steps of 1 %
Functions	Adjustable capacitive colour touch screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, motion sensor, encryption/overwriting of hard disk data (Data Security Kit), secure boot, run time integrity check, trusted platform modul (TPM), S/MIME etc.

DIMENSIONS/WEIGHT

Dimensions	790 x 602 x 665 mm (H x W x D)
Weight	approx. 95 kg

ENVIRONMENT

Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,750 W (2,400 W - 7008ci) max, approx. 660/780/990/1,140 W in operation (4008ci/5008ci/6008ci/7008ci), approx. 45 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 0.51/0.63/0.79/1.01 kWh/week (4008ci/5008ci/6008ci/7008ci)
Noise level	4008ci/5008ci/6008ci/7008ci: approx. (50.3/50) (51.9/51.6) (53.4/53) (54.3/54) dB(A) in operation (colour / b/w-mode), stand-by mode: 30.5/30.3/33.3/31.7 dB(A) (ISO 7779/9296)
Safety	GS/TÜV, CE

PRINT SYSTEM

Type	Integrated within the system
Print format	A6R-SRA3
Print resolution	600 x 600 dpi, max 4,800 equivalent x 1,200 dpi
Processor	ARM A53 1.6GHz
Interfaces	USB 3.0, USB-Host(4), Gigabit-Ethernet (10/100/1000BaseTX), SD-Card Slot
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019, Novell NetWare***, Linux, Mac OS 10.9
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 2.0, PRESCRIBE IIc
Functions	USB direct printing, PDF/XPS direct printing, super resolution imaging (only KX driver), SNMPv3, printing of e-mails, private printing, EcoPrint, barcode printing, Mobile Print (Android/iOS)/ Apple AirPrint, NFC, Wi-Fi Direct***

SCAN SYSTEM

Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 137 (simplex) or 274 (duplex) A4 originals/min in colour and b/w with DP-7170 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interface	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, Multiple cropping, Handwriting enhancement

OPTIONAL FAX SYSTEM 12

Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	170 MB
Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS

Original feeder	DP-7150 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7160 document processor with simultaneous duplex scanning (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²), DP-7170 document processor with simultaneous duplex scanning and multi-feed detection (A6R-A3, capacity: 320 sheet A4, paper weight 35-220 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4, not available for 7008ci), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7140 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7150 (capacity: 4,000 sheet A4, stapling max 100 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7140/7150, BF-730 brochure module for DF-7140 (max 20 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), BF-9100 brochure module for DF-7150 (max 20 sheet saddle stitching and folding A4/SRA3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7140, IS-7100 inserter (available for 6008ci/7008ci), ZF-7100 Z-fold unit (available for 6008ci/7008ci)
Job Separator	JS-7100 (100 sheet, 52-300 g/m ² , A6R-SRA3), JS-7110 inner shift tray (250 sheet, 52-300 g/m ² , A6R-SRA3)
Paper feed	PF-7140 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7150 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
Other options	Scan extension kit (A), Internet fax kit (A), Card authentication kit(B), Keyboard holder 10, Banner guide 10, UG-33 Thin-Print® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card (IEEE802.11b/g/n), IB-37 WLAN card (IEEE802.11a/b/g/n/ac, Wi-Fi direct) or IB-38 WLAN card**** (IEEE 802.11 b/g/n Wi-Fi direct), DT-730 (B) Document tray, NK-7120 Numeric Keyboard (10 keys), cabinet no. 81, HD-15 (320 GB HDD**), HD-16 (1 TB HDD**), Fiery® Controller (Printing System 17)

* Depending on operating status

** For copy, print, scan, fax

*** optional

**** IB-38 is only available for selected countries outside the EU that do not support the IB-37



Specifications subject to change without notice.

Image shows machine with optional accessories.



TA Triumph-Adler is the document business expert. We offer our clients individual analysis, consultancy and efficient document workflows – not only on paper, but also electronically and with long-term service. For whenever professional users manage, print, photocopy, fax, present or archive documents, or need to optimise processes, TA Triumph-Adler concepts and solutions are the first choice. Our customers benefit greatly from the user-optimised technologies offered by our innovative systems. TA Triumph-Adler and the TA Triumph-Adler logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names are the registered trademarks of their respective owners.

TA Triumph-Adler